



Pas Reform SmartPro™ Combi Incubator

For goose eggs

Designed to meet the specific requirements of small,
specialised hatcheries



Royal Pas Reform
Integrated Hatchery Solutions



SmartPro™ Combi Incubator

Setting and hatching functions in one cabinet

Benefits

The SmartPro™ Combi Incubator has been designed to incorporate the features and advantages of Pas Reform's larger SmartPro™ incubation technologies, to meet the specific requirements of small, specialised hatcheries. The Combi offers controlled setting and hatching functions in one cabinet and can be used for various species, including hen, ostrich, duck, goose or turkey. Flexible in operation, the unit can be used solely as a setter, a hatcher or as a combination of both. Easily manoeuvrable when fitted with large swivel wheels, the SmartPro™ Combi Incubator is supplied pre-tested, ready to plug in and start incubating.

How it works

- The SmartPro™ Combi Incubator is constructed from heavy duty, waterproof panels and equipped with electronic temperature and humidity controls
- The machine incorporates a reliable, fully automatic, mechanical turning device which rotates the eggs through 90° at programmable time periods
- SmartTouch™ multi-language user interface design makes operation simple and easily accessible to operators of all skill levels
- The Combi is shipped fully assembled, and is simple to install and operate

Related products

- ▶ Setter tray for goose
- ▶ SmartBasket™
- ▶ SmartTouch™



Technical Specifications

| | C-21 | C-41 | C-61 |
|-------------------------------------|--|--------------------|--------------------|
| Goose Egg capacity (56 tray) | | | |
| Setting | > 168 | > 280 | > 392 |
| Hatching | > 168 | > 336 | > 448 |
| Setting/Hatching | > 112/56 | > 224/56 | > 336/56 |
| Dimensions (LxWxH) | > 1640x810x1080 mm | > 1640x810x1340 mm | > 1620x810x1590 mm |
| Dimensions movable frame (optional) | > 1280x820x130 mm | > 1280x820x130 mm | > 1280x820x130mm |
| Electrical requirements | > 230 volts / 4 amp. / 50 Hz / 1 Ph + 0 + PE | | |
| Installed power | > 750W | | |
| Water temperature | > 12° - 15° C | | |
| Water pressure | > 2.5 bar | | |
| Water consumption | > 5 ltr/min | | |

Due to continuous product development specifications are subject to change without prior notice. Version 2020_03



Royal Pas Reform

Integrated Hatchery Solutions

Bovendorpsstraat 11
7038 CH Zeddum
The Netherlands

Phone +31 314 659 111
info@pasreform.com
www.pasreform.com