

# Pas Reform SmartPro™ Combi Incubator

For hen eggs

Designed to meet the specific requirements of small, specialised hatcheries





## **SmartPro™ Combi Incubator**

Setting and hatching functions in one cabinet

#### **Benefits**

The SmartPro™ Combi Incubator has been designed to incorporate the features and advantages of Pas Reform's larger SmartPro™ incubation technologies, to meet the specific requirements of small, specialised hatcheries. The Combi offers controlled setting and hatching functions in one cabinet and can be used for various species, including hen, ostrich, duck, goose or turkey. Flexible in operation, the unit can be used solely as a setter, a hatcher or as a combination of both. Easily manoeuvrable when fitted with large swivel wheels, the SmartPro™ Combi Incubator is supplied pretested, ready to plug in and start incubating.

#### How it works

- The SmartPro™ Combi Incubator is constructed from heavy duty, waterproof panels and equipped with electronic temperature and humidity controls
- The machine incorporates a reliable, fully automatic, mechanical turning device which rotates the eggs through 90° at programmable time periods
- SmartTouch™ multi-language user interface design makes operation simple and easily accessible to operators of all skill levels
- The Combi is shipped fully assembled, and is simple to install and operate

#### **Related products**

- ► SmartTray™ 150
- ▶ SmartBasket™
- ▶ SmartTouch™



### **Technical Specifications**

Hen egg capacity	C-21	C-41	C-61	C-82*
(150 tray)				
Setting	> 600	> 900	> 1,200	> 1,800
Hatching	> 600	> 900	> 1,200	
Setting/Hatching	> 300/150	> 600/150	> 900/150	
Dimensions (LxWxH)	> 1640x810x1080 mm	> 1640x810x1340 mm	> 1620x810x1590 mm	> 1620x810x1990 mm
Dimensions movable	> 1280x820x130 mm	> 1280x820x130 mm	> 1280x820x130mm	> 1280x820x130 mm
frame (optional)				

<sup>\*</sup> C-82 only suitable for incubation up to day 11

Electrical requirements > 230 volts / 4 amp. / 50 Hz / 1 Ph + 0 + PE Installed power > 750W

Water temperature > 12° - 15° C
Water pressure > 2.5 bar
Water consumption > 5 ltr/min



Bovendorpsstraat 11 7038 CH Zeddam The Netherlands

Phone +31 314 659 111 info@pasreform.com www.pasreform.com