

Pas Reform SmartCenterPro™

Hatchery Information System

A dynamic, web-based information system that gathers real-time data at every level of operations for fully comprehensive hatchery analysis and reporting





SmartCenterPro™

Incubation, automation and climate control in one network

Benefits

SmartCenterPro™ is a hatchery information system created to deliver precise, consistent process control, analysis and reporting for every level of hatchery operations. Incubation, climate control and hatchery automation systems can be fully optimised, seamlessly connected and data enabled. Every egg-to-chick journey and hatchery process, from the receipt of hatching eggs to sending the day old chicks to the farm, culminates in a unique cycle report, containing batch specific information on traceability, chick uniformity and hatcher climate, hatchery climate and alarms.



How it works

Three main program tiers provide rapid access to SmartCenterPro™'s complete information system:

Hatchery Overview:

- Continuously monitors incubators, hatchery automation and climate control systems
- Fine-tunes settings for optimum incubation conditions at all times

Hatchery Management:

 Manages key functions, from track & trace, alarm management and maintenance to breed specific incubation programming

Hatchery Analysis:

- Charts every process and event in day to day operations
- Produces real time management reports, with detailed, batch specific information for every hatch cycle

Related products

- SmartTouch™ user interface
- ▶ SmartSetPro™
- ▶ SmartHatchPro™
- ▶ SmartCount™
- ▶ Air Handling Unit
- Chiller

Technical Specifications

Housing > 19 inch rack (wall mount)

Measurements > 600 x 600 x 600

Connections > 1x LAN For office network and/or internet

> 1x LAN For a maximum of 250 SmartDrive

> 1x LAN
For a maximum of 250 SmartDrive™ user interfaces
> 4x RS422
For a maximum of 4 x 32 Navigator or HOM user nterfaces
> 1x Output
Potential free alarm contact (NC), for external buzzer, horn, etc
> 6x Inputs
6 auxiliary inputs for free use (NC), for connection with HAS/HVAC
> 2x modem
Voice alarm message / backup alarm modem (modalarm)

> Interpret

Requirements > Internet Fixed internet IP (ADSL or cable), ports 2020 /2022

> Power 230 Volt, 50/60 Hz + ground

> Cables To Navigator or HOM: 3 x 2 x 0.34 mm² shielded
To SmartPro™ or SmartDrive™; cat.5 Ethernet cable

To Backup alarm: 2 x 1 mm²

> Phone Line Analog phone line for voice alarm message system

Security > User name + password, Secure SSL internet connection

> Only accessible via computer with installed SSL certificate

> IP filter which can grant/deny access to SmartCenterPro™ web pages

Туре	Alarm horn connection	Voice alarm dialing	Maintenance module	Track & trace module*	SmartCount [†] connection	[™] Chiller connection	Air handling unit connection
Basic	Yes	No	No	No	Yes	No	No
Complete	Yes	Optional	Optional	Optional	Yes + data	Yes	Yes



Bovendorpsstraat 11 7038 CH Zeddam The Netherlands

Phone +31 314 659 111 info@pasreform.com www.pasreform.com

^{*} Only in combination with SmartTouch $^{\mathtt{m}}$ user interface